

# PRODUCT SPECIFICATIONS



## Main Unit

### Type

Color Laser Multifunctional

### Core Functions

Print, Copy, Scan, Send, Store, Fax (Line One Standard, Line Two Optional)

### Processor

Canon Dual Custom Processor (Shared)

### Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

### Memory

3.0 GB RAM

### Hard Disk Drive

250 GB

### Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n)

### Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 650 Sheets

Maximum: 2,300 Sheets

### Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette, 100-sheet Stack Bypass

### Optional:

550-sheet Paper Cassette (CASSETTE MODULE-AE1),  
550-sheet Paper Cassette with Cabinet (CASSETTE FEEDING UNIT-AJ1),  
Triple 550-sheet Paper Cassettes (CASSETTE FEEDING UNIT-AK1)

### Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets

Maximum: 500 Sheets (with STAPLE FINISHER-Z1)

### Finishing Capabilities

Standard: Collate, Group

With External

Finisher: Collate, Group, Offset, Staple

### Supported Media Types

Paper: Thin, Plain, Recycled, Color, Heavy,

Cassette: Pre-punched, Bond, Envelope

Stack Bypass: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Labels, Bond, Transparency, Envelope

Cassette Module-AE1: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Bond

Cassette Feeding Unit-AJ1: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Bond, Transparency

Cassette Feeding Unit-AK1: Thin, Plain, Recycled, Color, Heavy, Pre-punched, Bond

### Supported Media Sizes

Paper: Legal, Letter, Executive, Statement, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 7-1/2" to 8-1/2" x 14")

Stack Bypass: Legal, Letter, Executive, Statement, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 5-7/8" to 8-1/2" x 14"), Custom Size (3-7/8" x 5-7/8" to 8-1/2" x 14")

Cassette Module-AE1: Legal, Letter, Executive, Statement, Custom Size (3-7/8" x 7-1/2" to 8-1/2" x 14")

Cassette Feeding Unit-AJ1: Legal, Letter, Executive, Statement, Custom Size (3-7/8" x 7-1/2" to 8-1/2" x 14")

Cassette Feeding Unit-AK1: Legal, Letter, Executive, Statement, Custom Size (3-7/8" x 7-1/2" to 8-1/2" x 14")

### Supported Media Weights

Cassettes: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m<sup>2</sup>)

Stack Bypass: 16 lb. Bond to 80 lb. Cover (60 to 220 g/m<sup>2</sup>)

Duplexing: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m<sup>2</sup>)

### Print/Copy Speed (BW and Color)

C355iF: Up to 36 ppm (Letter);

Up to 29 ppm (Legal)

C255iF: Up to 26 ppm (Letter);

Up to 21 ppm (Legal)

### Warm-up Time

From Power On: 30 Seconds (C355iF)

34 Seconds (C255iF)

From Sleep Mode: 10 Seconds

Quick Startup Mode: 4 Seconds<sup>1</sup>

Mode:



## Dimensions (W x D x H)

Standard (Desktop): 20-1/8" x 25-1/8" x 25-5/8"  
(511 mm x 639 mm x 651 mm)

With Cassette Feeding Unit-AJI or AKI: 20-1/8" x 25-1/8" x 41-9/10"  
(511 mm x 639 mm x 1,064 mm)

## Installation Space (W x D)

Basic: 33-1/2" x 35-3/4" (852 mm x 908 mm)

With Staple Finisher-Z1: 55-3/8" x 35-3/4" (1,407 mm x 908 mm)

## Weight<sup>2</sup>

Standard (Desktop): Approx. 108 lb. (49 kg)

With Cassette Feeding Unit-AJI: Approx. 143.3 lb. (65 kg)

With Cassette Feeding Unit-AKI: Approx. 149.9 lb. (68 kg)

## Print Specifications

### Print Resolution (dpi)

1200 x 600

### Standard Page Description Languages

UFR II, PCL<sup>®</sup>6, Adobe<sup>®</sup>PS<sup>®</sup>3

### Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access<sup>3</sup>

### Supported File Types

PDF, TIFF, JPEG, EPS, XPS

### Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),<sup>4</sup> Barcode Fonts<sup>5</sup>

PS fonts: 136 Roman

### Operating System<sup>6</sup>

UFR II/PS: Server 2003/Server 2003 R2/Windows Vista<sup>®</sup>/Server 2008/Windows<sup>®</sup> 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/MAC OS X (10.6.8 or later)

PCL: Server 2003/Server 2003 R2/Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10

### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction

## Copy Specifications

### First-Copy-Out Time (Letter)

C355iF: As fast as 5.1 seconds (BW)/6.9 seconds (Color)

C255iF: As fast as 6.9 seconds (BW)/9.4 seconds (Color)

### Copy Resolution (dpi)

Reading: 600 x 600

Printing: 600 x 600

### Multiple Copies

Up to 999 copies

### Copy Exposure

Automatic or Manual (9 Levels)

### Magnification

25%-400% (1% Increments)

### Preset Reductions

25%, 50%, 64%, 73%, 78%

## Preset Enlargements

121%, 129%, 200%, 400%

## Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

## Special Copy Features

Two-Sided Original, Finishing, Job Build, N on 1, Density Adjustment, Original Type Selection, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Job Done Notice, Copy ID Card, Multi Sheet Feed Detection

## Scan Specifications

### Type

Single-pass Duplexing Automatic Document Feeder

### Document Feeder Paper Capacity

100 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

Legal, Letter, Statement

### Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 34 lb. Cover (50 to 128 g/m<sup>2</sup>)

CL Original: 17 lb. Bond to 34 lb. Cover (64 to 128 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

### Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows Vista/7/8/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2

### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

### Scan Speed (Letter)

Single-sided Scanning (BW/CL): 50 ipm (300 dpi)/30 ipm (600 dpi)

Double-sided Scanning (BW/CL): 100 ipm (300 dpi)/50 ipm (600 dpi)

## Send Specifications

### Destination

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax, IP Fax (Optional)

### Color Mode

Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and-White), Full color, Grayscale, and Black-and-White

### Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

### Communication Protocol

File: FTP, SMB, WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

### File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint<sup>®</sup>, Word)

Optional: PDF (Trace & Smooth, Encrypted), PDF/XPS (Digital Signature)

### Universal Send Features

Original Type Selection, Two-Sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Direct Send, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-To, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

## Fax Specifications

### Maximum Number of Connection Lines

2 (Line One Standard, Line Two Optional)

### Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

### Sending/Recording Size

Statement to Legal

### Fax Memory

Up to 30,000 Pages

### Speed Dials

Max. 200

### Group Dials/Destinations

Max. 199 Dials

### Sequential Broadcast

Max. 256 Addresses

### Memory Backup

Yes

### Fax Features

Original Type Selection, Two-Sided Original, Density for Scanning, Sharpness, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

## Store Specifications

### Mail Box Simple (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows Vista/7/8/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB

### Advanced Box Features

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

### Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in

Optional: uniFLOW

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)

Optional: IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

## Document

Standard:	Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration
Optional:	Encrypted PDF, Encrypted Secure Print, User and Device Signatures, Secure Watermarks, Document Scan Locking

## Environmental Specifications

### Operating Environment

Temperature:	50 to 86 °F
Humidity:	20 to 80 % RH (no condensation)

### Power Requirements

120-127V AC 60 Hz, 6.9 A

### Plug (Main Unit)

NEMA 5-15P

### Power Consumption

Maximum:	Approx. 1.5 kWh
Standby:	Approx. 38.9 W
Sleep Mode:	Approx. 0.8 W <sup>7</sup>
Typical Electricity Consumption (TEC) Rating:	1.2 kWh (C355iF)
	0.8 kWh (C255iF)

### Standards

ENERGY STAR® Certified  
Rated EPEAT® Silver<sup>8</sup>

## Consumables

### Toner

GPR-51 Toner

### Toner Yield (Estimated @ 5% Coverage)

Black:	19,000 Images
Color (C,M,Y):	21,500 Images

## Paper Supply Options

### CASSETTE FEEDING UNIT-AJ1

Paper Capacity:	550 Sheets [20 lb. Bond (80 g/m <sup>2</sup> )]
Paper Size:	Legal, Letter, Executive, Statement, and Custom Size [3-7/8" x 7-1/2" to 8-1/2" x 14" (98 x 190.5 to 216 x 355.6 mm)]
Paper Weight:	16 lb. Bond to 60 lb. Cover (60 to 163 g/m <sup>2</sup> )
Power Source:	From the Main Unit
Dimensions (W x D x H):	20-1/8" x 20" x 16-3/4" (511 mm x 508 mm x 425 mm)
Weight:	Approx. 35.3 lb. (16 kg)

### CASSETTE FEEDING UNIT-AK1

Paper Capacity:	1,650 Sheets [20 lb. Bond (80 g/m <sup>2</sup> )]
Paper Size:	Legal, Letter, Executive, Statement, and Custom Size [3-7/8" x 7-1/2" to 8-1/2" x 14" (98 x 190.5 to 216 x 355.6 mm)]
Paper Weight:	16 lb. Bond to 60 lb. Cover (60 to 163 g/m <sup>2</sup> )
Power Source:	From the Main Unit
Dimensions (W x D x H):	20-1/8" x 20" x 16-3/4" (511 mm x 508 mm x 425 mm)
Weight:	Approx. 41.9 lb. (19 kg)

### CASSETTE MODULE-AE1

Paper Capacity:	550 Sheets [20 lb. Bond (80 g/m <sup>2</sup> )]
Paper Size:	Legal, Letter, Executive, Statement, and Custom Size [3-7/8" x 7-1/2" to 8-1/2" x 14" (98 x 190.5 to 216 x 355.6 mm)]
Paper Weight:	16 lb. Bond to 60 lb. Cover (60 to 163 g/m <sup>2</sup> )
Power Source:	From the Main Unit
Dimensions (W x D x H):	20-1/8" x 20" x 6-1/4" (511 mm x 508 mm x 159 mm)
Weight:	Approx. 22 lb. (10 kg)

## Output Options

### STAPLE FINISHER-Z1 (External)

Number of Trays:	1
Tray Capacity:	500 Sheets
Paper Weight:	16 lb. Bond to 80 lb. Cover (60 to 220 g/m <sup>2</sup> )
Staple Position:	Corner
Staple Capacity:	30 Sheets [Up to 28 lb. Bond (105 g/m <sup>2</sup> )]
Dimensions (W x D x H):	21-7/8" x 18-1/8" x 11-7/8" (555 mm x 459 mm x 301 mm)
Weight:	Approx. 30.9 lb (14 kg)

## Hardware Options

### Card Readers

IC CARD READER ATTACHMENT-C1
MiCARD PLUS PROXIMITY CARD READER
COPY CARD READER-F1
COPY CARD READER ATTACHMENT-B5

## Security Options

### Document Security

DOCUMENT SCAN LOCK KIT-B1
SECURE WATERMARK-B1
ENCRYPTED SECURE PRINT SOFTWARE-D1
IR-ADV SECURITY KIT-RI FOR IEEE 2600.1 COMMON CRITERIA CERTIFICATION <sup>9</sup>

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1

### Barcode Printing

BARCODE PRINTING KIT-D1

### Fax Accessories

SUPER G3 2ND LINE FAX BOARD-AT1
IP FAX EXPANSION KIT-B1

## Other Options

### Staples

STAPLE-P1<sup>10</sup>

## Footnotes

- <sup>1</sup> Time from device power-on to when copy jobs can be programmed.
- <sup>2</sup> Includes consumables.
- <sup>3</sup> PDF print from Web sites is supported.
- <sup>4</sup> Requires the optional PCL International Font Set-A1.
- <sup>5</sup> Requires the optional Barcode Printer Kit-D1.
- <sup>6</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- <sup>7</sup> 0.8 W sleep mode not available in all circumstances due to certain settings.
- <sup>8</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).
- <sup>9</sup> Will launch at a later date.
- <sup>10</sup> Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon, imageRUNNER, imageWARE, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. iF Design Award 2017 is for third generation imageRUNNER ADVANCE Multifunction office systems. Google Cloud Print™ is either a registered trademark or trademark of Google Inc. AirPrint and the AirPrint logo are trademarks of Apple Inc. Adobe® and PostScript® 3™ are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft® and PowerPoint® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. PCL® is a registered trademark of Hewlett-Packard Company. All other referenced product names and marks are trademarks of their respective owners. All features presented may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.  
©2017 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

