![brother at your side]

Brother HL-L5210DW laser printer 1200 x 1200 DPI A4 Wi-Fi

Brand : Brother **Product code:** HL-L5210DW

Product name : HL-L5210DW

Laser, 1200 x 1200 dpi, USB 2.0, LAN, WLAN, LCD
Brother HL-L5210DW. Print technology: Laser. Number of print cartridges: 1. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A4. Print speed (black, normal quality, A4/US Letter): 48 ppm, Duplex printing. Wi-Fi. Product colour: Black, White

Printing

Colour *	✗
Print technology *	Laser
Duplex printing *	✔
Maximum resolution *	1200 x 1200 DPI
Print speed (black, normal quality, A4/US Letter) *	48 ppm

Features

Printing colours *	Black
Number of print cartridges *	1
Page description languages *	BR-Script 3, PCL 6, PDF, XPS

Input & output capacity

Total number of input trays *	1
Total input capacity *	250 sheets
Total output capacity *	150 sheets
Multi-Purpose tray	✔
Multi-Purpose tray input capacity	100 sheets

Paper handling

Maximum ISO A-series paper size *	A4
Paper tray media types *	Envelopes, Letterhead, Plain paper, Recycled paper, Thin paper
ISO A-series sizes (A0...A9) *	A4, A5, A6
Non-ISO print media sizes	Folio, Legal, Letter
JIS B-series sizes (B0...B9)	B5
Envelopes sizes	C5, Com-10, DL, Monarch

Ports & interfaces

USB port *	✔
USB connector	USB Type-A / USB Type-B

Network

Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Security algorithms	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP, WPA3-SAE
Supported network protocols (IPv4)	ARP, RARP, BOOTP, DHCP, APIPA (Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/v3, ICMP, Web Services (Print), CIFS client, SNTP client, Syslog
Supported network protocols (IPv6)	NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, FTP Server, TELNET Server, HTTP/HTTPS server, TFTP client and server, SMTP Client, SNMPv1/v2c/v3, ICMPv6, Web Services (Print), CIFS Client, SNTP Client, Syslog

Performance

Internal memory *	512 MB
Sound pressure level (printing)	54 dB

Design

Market positioning *	Home & office
Product colour *	Black, White
Built-in display *	✔
Colour display	✗

Network

Wi-Fi *	✔
Ethernet LAN *	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s

Power

Power consumption (printing) *	670 W
AC input voltage	220 - 240 V
AC input frequency	50/60 Hz

System requirements

Windows operating systems supported	Windows 10, Windows 11

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Storage temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	35 - 85%

Weight & dimensions

Width	373 mm
Depth	388 mm
Height	257 mm

4977766815130

0012502666493

012502666493