Canon i-SENSYS MF754Cdw Laser A4 1200 x 1200 DPI 33 ppm Wifi

Marque : Canon

Famille de produit: i-SENSYS

Code produit: 5455C021

Nom du produit : MF754Cdw

Canon i-SENSYS MF754Cdw. Technologie d'impression: Laser, Impression: Impression couleur, Résolution maximale: 1200 x 1200 DPI. Copier: Copie couleur, Résolution max. des copies: 600 x 600 DPI. Numérisation: Numérisation couleur, Résolution de numérisation optique: 600 x 600 DPI. Télécopier: Télécopie couleur. Fonctions recto verso: Copie. Taille de papier de série A ISO maximum: A4. Wifi. Couleur du produit: Noir, Blanc

Printing		Paper handling	
Print technology * Printing * Maximum resolution * Print speed (black, normal quality, A4/US Letter) * Warm-up time Time to first page (black, normal)	Laser Colour printing 1200 x 1200 DPI 33 ppm 14 s 7.1 s	Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes Envelopes sizes	Coated paper, Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper, Thin paper A4, A5, A6 B5 Legal, Letter, Oficio, Statement C5, Com-10, DL, Monarch
Time to first page (colour, normal)	7.1 s	Ports & interfaces	
Secure printing	✓	USB port	1
Copying		USB 2.0 ports quantity	1
Duplex copying *	✓	Network	
Duplex copying mode Copying * Maximum copy resolution * Maximum number of copies Copier resize N-in-1 copy function N-in-1 copy function (N=)	Auto Colour copying 600 x 600 DPI 999 copies 25 - 400% ✓ 2, 4	Wi-Fi * Ethernet LAN * Cabling technology Ethernet LAN data rates Wi-Fi standards Mobile printing technologies	 10/100/1000Base-T(X) 10,100,1000 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n) Apple AirPrint, Canon PRINT Business, Mopria Print Service
ID-card copy function	1	Performance	
Scanning		Internal memory *	1024 MB
Scanning *Colour scanningOptical scanning resolution *600 x 600 DPlScanner type *ADF scannerScan toCloud, E-mail, FTP, PC, USBInput colour depth24 bitOutput colour depth24 bitGreyscale levels256	Built-in processor Processor frequency Sound pressure level (printing) Sound pressure level (duplex printing) Sound power level (standby) Design	 1200 MHz 51 dB 51 dB 29 dB 	
Scan drivers	ICA, TWAIN, WIA	Product colour *	Black, White
Fax Faxing * Fax transmission speed Modem speed	Colour faxing 3 sec/page 33.6 Kbit/s	Market positioning * Built-in display * Display Control type	Business ✓ LCD Touch
Fax memory	512 pages	Power	
Speed dialling	√	Power consumption (max)	1380 W
Features Recommended duty cycle Maximum duty cycle * Duplex functions * Printing colours * Page description languages Input & output capacity	750 - 4000 pages per month 50000 pages per month Copy Black, Cyan, Magenta, Yellow PCL 5c, PCL 6, PostScript, UFRII	Power consumption (printing) Power consumption (standby) Power consumption (sleep) Energy Star Typical Electricity Consumption (TEC) AC input voltage AC input frequency	700 W 24 W 1 W 0.3 kWh/week 220 - 240 V 50 - 60 Hz
Total number of input trays * Total input capacity *	1 250 sheets		

Input & output capacity		System requirements	
Total output capacity *	150 sheets	Windows operating systems supported Mac operating systems supported	Windows 10, Windows 8.1, Windows
Multi-Purpose tray	✓		11
Multi-Purpose tray input capacity	50 sheets		Mac OS X 10.13 High Sierra, Mac OS X 10.4 Tiger, Mac OS X 11.0 Big Sur, Mac OS X 10.14 Mojave, Mac OS X 10.5 Leopard, Mac OS X 12.0 Monterey, Mac OS X 10.15 Catalina, Mac OS X 10.6 Snow Leopard, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac OS X 10.2 Jaguar, Mac OS X 10.8 Mountain Lion, Mac OS X 10.12 Sierra, Mac OS X 10.3 Panther, Mac OS X 10.9 Mavericks
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	50 sheets		
Maximum input capacity	850 sheets		
Paper handling			
Maximum ISO A-series paper size *	Α4		
		Linux operating systems supported	1

Operational conditions

Width

Depth

Height

Weight

Operating relative humidity (H-H)

Operating temperature (T-T)
Weight & dimensions

Windows Server 2019, Windows Server operating systems supported Server 2012 R2, Windows Server 2016, Windows Server 2012

> 20 - 80% 10 - 30 °C


425 mm

461 mm

430 mm

23.6 kg

Publication date: 21-FEB-2025. Prints or copies of Information are only valid on the printed Publication date



8714574670935

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.